

# Material Safety Data Sheet

# U.S. Department of Labor

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Standard must be consulted for specific requirements.

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved OMB No. 1218-0072

IDENTITY (*As Used on Label and List*)

**Diazo Photo Emulsion (component of #4559, 4520, 4523, 4524, 4522 & 4526; 4579)**

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

**Section I** Manufacturer's Name

**Speedball Art Products, LLC**

Emergency Telephone Number

**704-838-1475**

Address (*Number, Street, City, State, and ZIP Code*)

**2226 Speedball Road Statesville, NC 28677 USA**

Telephone Number for Information

**704-838-1475**

Date Prepared: **March 1, 2004**

Signature of Preparer (*optional*)

## Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	%( <i>optional</i> )
<b>Ethyl Alcohol (CAS #64-17-5)</b>	<b>N/A</b>	<b>1000ppm</b>	<b>N/A</b>	<b>4%</b>

**This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.**

## Section III - Physical/Chemical Characteristics

Boiling Point	<b>212°F</b>	Specific Gravity (H <sub>2</sub> O = 1)	<b>1.1</b>
Vapor Pressure (mm Hg.)	<b>N/A</b>	Melting Point	<b>&lt;32°F</b>
Vapor Density (AIR = 1)	<b>Less than 1</b>	Evaporation Rate (Butyl Acetate = 1)	<b>Less than 1</b>
Solubility in Water	<b>Dilutable</b>	Appearance and Odor	<b>Light Blue with faint odor</b>

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) <b>N/A</b>	Flammable Limits <b>N/A</b>	LEL <b>N/A</b>	UEL <b>N/A</b>
Extinguishing Media <b>N/A</b>			
Special Fire Fighting Procedures <b>Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.</b>			
Unusual Fire and Explosion Hazards <b>Material can spatter above 212°F. Film can burn.</b>			

(Reproduce locally)

OSHA 174, Sept. 1985

Stability	Unstable	Stable ✓	Conditions to Avoid <b>Onset of decomposition is 350°F</b>
Incompatibility ( <i>Materials to Avoid</i> ) N/A			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A

## Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards ( <i>Acute and Chronic</i> ) N/A			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure N/A			
Emergency and First Aid Procedures N/A			

## Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled <b>Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.</b>
Waste Disposal Method <b>Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.</b>
Precautions to Be taken in Handling and Storing <b>Keep from freezing-product may coagulate</b>
Other Precautions N/A

## Section VIII - Control Measures

Respiratory Protection ( <i>Specify Type</i> ) <b>None required with adequate ventilation &amp; normal usage conditions.</b>			
Ventilation	Local Exhaust <b>Adequate</b>	Special	N/A
	Mechanical ( <i>General</i> ) N/A	Other	N/A
Protective Gloves <b>Impervious</b>	Eye Protection <b>Safety Glasses or goggles</b>		
Other Protective Clothing or Equipment N/A			
Work/Hygienic Practices <b>Use protective cream where excessive skin contact is likely.</b>			