



## SAFETY DATA SHEET

### Polwhite™ B

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name	Polwhite™ B
Substance Name	Kaolin
Chemical name	Hydrated aluminium silicate
Synonyms; trade names	China clay
REACH registration notes	Exempted in accordance with REACH Annex V.7
CAS number	1332-58-7
EC number	310-194-1
Molecular Weight	Unspecified for this UVCB substance

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	A functional additive
Uses advised against	No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

Supplier	IMERYS Minerals Ltd Par Moor Centre Par Moor Road Par, Cornwall England PL24 2SQ Tel. +44(0)1726 818000 Fax. +44(0)1726 811200 SDS.expert@imerys.com
----------	--

##### 1.4. Emergency telephone number

Emergency telephone	CHEMTREC + 1 703 527 3887
---------------------	---------------------------

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified

**Human health** This product does not meet the criteria for classification as hazardous as defined in the Regulation EC 1272/2008. It is recommended that due regard be taken of the specified constituents in deriving an Occupational Exposure Standard for the workplace.

## Polwhite™ B

<b>Environmental</b>	The product is not expected to be hazardous to the environment.
<b>Physicochemical</b>	This product should be handled with care to avoid dust generation.

### 2.2. Label elements

<b>EC number</b>	310-194-1
<b>Hazard statements</b>	NC Not Classified

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

<b>KAOLIN</b>	<b>100%</b>
CAS number: 1332-58-7	EC number: 310-194-1
<b>Classification</b> Not Classified	

The full text for all hazard statements is displayed in Section 16.

<b>Product name</b>	Polwhite™ B
<b>Chemical name</b>	Hydrated aluminium silicate
<b>REACH registration notes</b>	Exempted in accordance with REACH Annex V.7
<b>CAS number</b>	1332-58-7
<b>EC number</b>	310-194-1
<b>Ingredient notes</b>	This product is 100% Kaolin, which is a UVCB substance sub-type 4.
<b>Composition comments</b>	This product contains less than 1% quartz (fine fraction) Quartz: CAS-No.: 14808-60-7 EC No.: 238-878-4.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	No acute and delayed symptoms and effects are observed. Consult a physician for all exposures except for minor instances.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Ingestion</b>	No special treatment required. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
<b>Skin contact</b>	No special first aid measures necessary.
<b>Eye contact</b>	Do not rub eye. Rinse with copious quantities of water and seek medical attention if irritation persists.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

## Polwhite™ B

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** The product is non-combustible. No specific extinguishing media is needed. Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** No restriction on the extinguishing media to be used.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Non combustible. No hazardous thermal decomposition.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** No specific fire-fighting protection is required. Use an extinguishing agent suitable for the surrounding fire. Product on floor when wetted will become slippery and may present a hazard; wear anti-slip boots.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid airborne dust generation, wear personal protective equipment in compliance with national legislation.

#### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Avoid dry sweeping and use water spraying or vacuum cleaning systems to prevent airborne dust generation. Alternatively shovel into bags.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Avoid airborne dust generation. Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment. Handle packaged products carefully to prevent accidental bursting. If you require advice on safe handling techniques, please contact your supplier. Do not eat, drink and smoke in work areas; wash hands after use; remove contaminated clothing and protective equipment before entering eating areas. For personal protection, see Section 8.

**Advice on general occupational hygiene** Keep dust levels to a minimum. Minimize dust generation. General occupational hygiene measures are required. These include good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices). Shower and change clothes at end of work shift. Change work clothing daily before leaving workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in a dry covered area. Minimise airborne dust generation and prevent wind dispersal during loading and unloading. Keep containers closed and store packaged products so as to prevent accidental bursting.

#### 7.3. Specific end use(s)

**Usage description** If you require advice on specific uses, please contact your supplier.

### SECTION 8: Exposure Controls/personal protection

## Polwhite™ B

### 8.1. Control parameters

#### Occupational exposure limits

##### **KAOLIN**

Long-term exposure limit (8-hour TWA): WEL 2 mg/m<sup>3</sup> respirable dust

##### **Inorganic dust**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

##### **Quartz**

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m<sup>3</sup> respirable dust

WEL = Workplace Exposure Limit

#### **Ingredient comments**

Maintain personal exposure below occupational exposure limits for dust (inhalable and respirable) as dictated in the national legislation.

### 8.2. Exposure controls

#### **Appropriate engineering controls**

Minimise airborne dust generation. Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Apply organisational measures, e.g. by isolating personnel from dusty areas. Remove and wash soiled clothing. Observe any occupational exposure limits for the product or ingredients. ...

#### **Eye/face protection**

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield. Contact lenses should not be worn when working with this product.

#### **Hand protection**

Appropriate protection (e.g. gloves, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin. Wash hands at the end of each work session. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Neoprene. Rubber (natural, latex).

#### **Other skin and body protection**

For skin, normal work clothes are appropriate.

#### **Hygiene measures**

When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

#### **Respiratory protection**

Local ventilation to control airborne dust levels below occupational exposure limits is recommended. In case of exposure, where engineering controls are insufficient, the use of Respiratory Protective Equipment (RPE) is recommended. A risk assessment process must be followed to ensure adequate protection from the airborne dust. The type of RPE must suit the work situation and the specific requirements of the wearer. Other environmental conditions should also be considered. The minimum "Assigned Protection Factor" (APF) required will depend on the measured or predicted occupational exposure levels divided by the OEL detailed in section 8.1. Filters specified as FFP2 and P2 have an APF of 10. Correctly fitted, these would reduce the exposure to the wearer down to one tenth of the working atmosphere. Depending on the assessment of the exposure, a lesser or higher efficiency of filter may be required. The manufacturer's instructions and regulatory guidance regarding duration of use and correct fitting should be followed. The wearer of the selected RPE should receive training before use.

#### **Environmental exposure controls**

All ventilation systems should be filtered before discharge to atmosphere. Avoid releasing into the environment. Contain the spillage.

## **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

## Polwhite™ B

<b>Appearance</b>	Powder
<b>Colour</b>	White/off-white.
<b>Odour</b>	Almost odourless.
<b>pH</b>	5-8 @ 10 % Slurry
<b>Melting point</b>	> 450 °C EU Method A1
<b>Initial boiling point and range</b>	not applicable (Solid with a melting point > 450°C)
<b>Flash point</b>	not applicable (Solid with a melting point > 450°C)
<b>Evaporation rate</b>	not applicable (Solid with a melting point > 450°C)
<b>Flammability (solid, gas)</b>	Non flammable EU Method A1
<b>Upper/lower flammability or explosive limits</b>	Non explosive (void of any chemical structures commonly associated with explosive properties)
<b>Vapour pressure</b>	not applicable (Solid with a melting point > 450°C)
<b>Vapour density</b>	not applicable (Solid with a melting point > 450°C)
<b>Relative density</b>	2.6 g/cm <sup>3</sup>
<b>Bulk density</b>	0.5 - 0.8 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	<1 mg/litre @ 20 °C EU Method A6
<b>Partition coefficient</b>	Not applicable (inorganic substance)
<b>Auto-ignition temperature</b>	No relative self-ignition temperature below 400 °C EU method A16
<b>Decomposition Temperature</b>	Not applicable (Solid with a melting point > 450°C)
<b>Viscosity</b>	Not applicable (Solid with a melting point > 450°C)
<b>Explosive properties</b>	There are no chemical groups present in the product that are associated with explosive properties.
<b>Oxidising properties</b>	There are no chemical groups present in the product that are associated with oxidising properties.

### 9.2. Other information

**Other information** No information required.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** There are no known reactivity hazards associated with this product.

### 10.4. Conditions to avoid

**Conditions to avoid** No particular incompatibility.

### 10.5. Incompatible materials

## Polwhite™ B

**Materials to avoid** No particular incompatibility.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Inhalation** Dust in high concentrations may irritate the respiratory system.

**Ingestion** No harmful effects expected from quantities likely to be ingested by accident.

**Skin contact** Prolonged contact may cause dryness of the skin.

**Eye contact** Particles in the eyes may cause irritation and smarting.

### Toxicological information on ingredients.

#### KAOLIN

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> >2000 mg/kg, Oral, Rat OECD 420

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> >2000 mg/kg, Dermal, Rat OECD 402

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** LC<sub>50</sub> >5.07 mg/l, Inhalation, Rat OECD 436

##### Skin corrosion/irritation

**Skin corrosion/irritation** Kaolin is not irritating to skin (OECD 404, rabbit).

##### Serious eye damage/irritation

**Serious eye damage/irritation** Kaolin is not irritating to eye (OECD 405, rabbit).

##### Respiratory sensitisation

**Respiratory sensitisation** Mouse: Not sensitising. OECD 429

##### Skin sensitisation

**Skin sensitisation** Local Lymph Node Assay (LLNA) - Mouse: Not sensitising. OECD 429

##### Germ cell mutagenicity

**Genotoxicity - in vitro** No specific test data are available.

**Genotoxicity - in vivo** No specific test data are available.

##### Carcinogenicity

**Carcinogenicity** In studies where kaolin has been administered via intratracheal installation, kaolin behaves as a poorly soluble particulate of low toxicity with inflammatory responses of lung tissue. Epidemiological studies covering a large number of workers did not reveal an explicit association between kaolin exposure and tumour formation. In summary, no concern on carcinogenicity is triggered by animal studies or by epidemiological findings

##### Reproductive toxicity

## Polwhite™ B

**Reproductive toxicity - fertility** No specific test data are available.

### Specific target organ toxicity - single exposure

**STOT - single exposure** No organ toxicity observed in acute tests.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on the results from animal studies (mainly via intratracheal administration) it seems that the severity of effects seen in the lungs may be related to the level of crystalline silica (fine fraction) present in the material as an accessory mineral. Epidemiological studies show that exposure to high levels of kaolin dust may lead to pneumoconiosis. Results indicate that the effects from kaolin exposure are typical of those seen with poorly soluble particles under conditions of lung overload i.e. the lungs clearance capacity has been exceeded. It is likely that the severity of any effects are related to the level of crystalline silica (fine fraction) present in the material as an accessory mineral.

### Aspiration hazard

**Aspiration hazard** No specific test data are available.

## SECTION 12: Ecological Information

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

### 12.1. Toxicity

#### Ecological information on ingredients.

#### KAOLIN

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: >1000 mg/l, Oncorhynchus mykiss (Rainbow trout)  
OECD 203

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: >1000 mg/l, Daphnia magna  
OECD 202

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: >1000 mg/l, Freshwater algae  
OECD 201

**Acute toxicity - microorganisms** No specific test data are available.

#### Chronic aquatic toxicity

**Chronic toxicity - fish early life stage** No specific test data are available.

**Chronic toxicity - aquatic invertebrates** No specific test data are available.

**Toxicity to soil** No specific test data are available.

**Toxicity to terrestrial plants** No specific test data are available.

### 12.2. Persistence and degradability

**Persistence and degradability** The product is not biodegradable.

#### Ecological information on ingredients.

## Polwhite™ B

### KAOLIN

**Persistence and degradability** The substance is inorganic and therefore will not undergo abiotic degradation.

**Biodegradation** The substance is inorganic and therefore will not undergo biodegradation.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** The product does not contain any substances expected to be bioaccumulating.

**Partition coefficient** Not applicable (inorganic substance)

#### Ecological information on ingredients.

### KAOLIN

**Bioaccumulative potential** Not relevant for inorganic substances.

**Partition coefficient** Not applicable (inorganic substance)

#### 12.4. Mobility in soil

**Mobility** The product is insoluble in water.

#### Ecological information on ingredients.

### KAOLIN

**Mobility** Kaolin is almost insoluble and thus presents a low mobility in most soils.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### Ecological information on ingredients.

### KAOLIN

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

#### Ecological information on ingredients.

### KAOLIN

**Other adverse effects** None known.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**General information** This mineral can be disposed of as a non toxic/inactive material in approved landfill sites in accordance with local regulations. Dust formation from residues in packaging should be avoided and suitable worker protection assured. Store used packaging in enclosed receptacles. The re-use of packaging is not recommended. Recycling and disposal of packaging should be carried out by an authorised waste management company. Comply with local regulations for disposal



## Polwhite™ B

**Disposal methods** Where possible, recycling is preferable to disposal. Can be disposed of in compliance with local regulations.

### SECTION 14: Transport information

**General** The material is not classified as a dangerous substance and no restrictions apply for land/sea/air transportation (IMDG, IATA, ADR/RID). Avoid generation and spreading of dust.

#### 14.1. UN number

Kaolin is not classified as hazardous for transport and does not have a UN Number

#### 14.2. UN proper shipping name

No information required.

#### 14.3. Transport hazard class(es)

ADR, IMDG, ICAO/IATA, RID : All not classified

#### 14.4. Packing group

No information required.

#### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

#### 14.6. Special precautions for user

Avoid any release of dust during transportation, by using air-tight tanks for powders and covered trucks for other dry forms.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** No information required.

**Annex II of MARPOL 73/78  
and the IBC Code**

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** EH40/2005 Workplace exposure limits.  
Health and Safety at Work etc. Act 1974 (as amended).  
The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).

**EU legislation** Exempted in accordance with REACH Annex V.7

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

## Polwhite™ B

### Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service.

EC: European Commission

EC<sub>50</sub>: 50% of maximal Effective Concentration.

FFP: Filtering Face Piece

IMDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association.

LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.

OECD: Organisation for Economic Co-operation and Development

OEL: Occupational Exposure Limit

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

SDS: Safety Data Sheet

TWA: Time Weighted Average

UVCB: Unknown Variable Composition or Biological

## Polwhite™ B

### General information

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations. A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from <http://www.nepsi.eu> and provide useful information and guidance for the handling of products containing crystalline silica (fine fraction). Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers. Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In 2009, in the Monographs 100 series, IARC confirmed its classification of Silica Dust, Crystalline, in the form of Quartz and Cristobalite (IARC Monographs, Volume 100C, 2012). In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003). So there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required. Health & Safety Executive: Detailed reviews of the scientific evidence on the health effects of crystalline silica have been published by HSE (Health and Safety Executive, UK) in the Hazard Assessment Documents EH75/4 (2002) and EH75/5 (2003). The HSE points out on its website that "Workers exposed to fine dust containing quartz are at risk of developing a chronic and possibly severely disabling lung disease known as "silicosis"." In addition to silicosis, there is now evidence that heavy and prolonged workplace exposure to dust containing crystalline silica can lead to an increased risk of lung cancer. The evidence suggests that an increased risk of lung cancer is likely to occur only in those workers who have developed silicosis.

### Revision comments

Most of the 16 SECTIONS have been updated and formatted according to the revised ECHA Guidance on the compilation of safety data sheets (version 3.0 of August 2015). Therefore, this SDS has been completely redrafted and replaces the former SDS supplied.

### Revision date

06/12/2017

### Revision

8

### SDS number

10440

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.