

**SCREEN STRIP 1:50**

Stripper solution

**DESCRIPTION**

Stripping solution to remove emulsions of quick action.

**RECOMMENDED APPLICATION**

|                                   |            |
|-----------------------------------|------------|
| To remove non catalysed emulsions | Excellent. |
| To remove catalysed emulsions     | No.        |

**CHARACTERISTICS**

|               |             |
|---------------|-------------|
| Colour        | Colourless. |
| Odour         | Soft.       |
| Physical form | Liquid.     |
| Irritating    | Yes.        |

**PACKAGING**

|           |                 |
|-----------|-----------------|
| 20 L. box | 20 units x 1 L. |
| 20 L. box | 4 units x 5 L.  |

**ALTERNATIVE PRODUCT**

|              |  |
|--------------|--|
| SERICERO DRY |  |
| SERICERO GEL |  |

**INSTRUCTIONS OF USE**

Dilute 1 part of SCREEN STRIP 1:50 in 50 parts of water. Sprinkle both sides of the coated screen, leave 5 minutes and rinse with pressure water. With big screens use electric or mechanical sprayer to greatest efficiency.

In case of hard emulsions, dilute 1:40 ( 1 part of SCREEN STRIP 1:50 in 40 parts of water ) to get a more energetic stripping.

**ADDITIONAL INFORMATION**

Safety data sheet is available through Kopimask or your nearer supplier.

KOPIMASK, S.A. Ph. 00 34 93 863 93 50 Fax 00 34 93 864 94 34 e-mail [kopimask@kopimask.es](mailto:kopimask@kopimask.es)

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO 9001:2000 N°: E204216



[www.kopimask.com](http://www.kopimask.com)